


REBITES DE AÇO INOX COM MANDRIL DE AÇO INOX

Rebites padrão (cabeça abaulada)

Corpo: aço inox polido

Mandril: aço inox polido



Linha	Rebite (D x L) mm	Código Produto	Diâmetro corpo +0,08 - 0,10 mm	Comprimento o corpo +0,8 - 0,2 (mm)	Espessura Rebitável (mm)	Diâmetro Aba (mm)	Tração (kgf)	Cisalhamento (kgf)
3,2 Dia.furo 3,3 mm	3,2 x 6	6230602.01000	3,2	6,0	0,5 - 3,5	6,0 +0,5 - 0,3	255	193
	3,2 x 8	6231101.01000		8,0	3,5 - 4,5			
	3,2 x 10	6231402.01000		10,0	4,5 - 6,0			
	3,2 x 12	6231802.01000		12,0	6,0 - 9,0			
	3,2 x 15	6232400.01000		15,0	9,0 - 12,0			
	3,2 x 18			18,0	12,0 - 15,0			
4,0 Dia.furo 4,1 mm	4,0 x 6	6240601.01000	4,0	6,0	0,5 - 2,0	7,5 +0,5 - 0,3	367	275
	4,0 x 7	6240802.01000		7,0	1,0 - 3,0			
	4,0 x 8	6241001.01000		8,0	2,0 - 4,0			
	4,0 x 10	6241401.01000		10,0	4,0 - 6,0			
	4,0 x 12	6241802.01000		12,0	6,0 - 8,0			
	4,0 x 14	6242201.01000		14,0	8,0 - 10,0			
	4,0 x 16	6242603.01000		16,0	10,0 - 12,0			
4,8 Dia.furo 4,9 mm	4,8 x 06	6250601.00500	4,8	6,0	0,5 - 1,0	9,0 +0,5 - 0,3	510	408
	4,8 x 08	6251001.00500		8,0	0,5 - 3,0			
	4,8 x 10	6251401.00500		10,0	3,0 - 5,0			
	4,8 x 12	6251802.00500		12,0	5,0 - 7,0			
	4,8 x 14	6252201.00500		14,0	7,0 - 9,0			
	4,8 x 16	6252601.00500		16,0	9,0 - 11,0			
	4,8 x 20	6253403.00500		20,0	11,0 - 15,0			
	4,8 x 22	6253601.00500		22,0	15,0 - 17,0			
	4,8 x 25	6253901.00500		25,0	15,0 - 20,0			

* outros comprimentos de rebites sob consulta